

**Genetron® 124**

Version 2

Revision Date 11/15/2007

Print Date 11/15/2007

**SECTION 1. PRODUCT AND COMPANY IDENTIFICATION**

Product name : Genetron® 124  
MSDS Number : 000000009886  
Product Use Description : Refrigerant, Carrier gas

Company : Honeywell International, Inc.  
101 Columbia Road  
Morristown, NJ 07962-1057

For more information call : 800-522-8001  
(Monday-Friday, 9:00am-5:00pm)

**In case of emergency call : Medical: 1-800-498-5701**  
: **Transportation: 1-800-424-9300 or 703-527-3887**  
: (24 hours/day, 7 days/week)

**SECTION 2. HAZARDS IDENTIFICATION****Emergency Overview**

Form : Liquefied gas

Color : colourless

Odor : weak

Hazard Summary : Warning! Container under pressure. This product is not flammable at ambient temperatures and atmospheric pressure. Gas reduces oxygen available for breathing. Causes asphyxiation in high concentrations. The victim will not realize that he/she is suffocating. Inhalation may cause central nervous system effects. May cause cardiac arrhythmia. May cause drowsiness and dizziness. Do not breathe vapour. Avoid contact with skin, eyes and clothing. At higher temperatures, (>250°C), decomposition products may include hydrochloric acid (HCl), hydrofluoric acid (HF) and carbonyl halides. The ACGIH Threshold Limit Values (2007) for Hydrogen Fluoride are TLV-TWA 0.5 ppm and Ceiling Exposure Limit 2 ppm.

**Potential Health Effects**

Skin : Avoid skin contact with leaking liquid (danger of frostbite).  
May cause frostbite.  
Irritating to skin.

Eyes : Causes severe eye irritation.  
May cause frostbite.

Ingestion : Unlikely route of exposure.  
Effects due to ingestion may include:

**Genetron® 124**

Version 2

Revision Date 11/15/2007

Print Date 11/15/2007

Gastrointestinal discomfort

Inhalation : Gas reduces oxygen available for breathing. Causes asphyxiation in high concentrations. The victim will not realize that he/she is suffocating. Inhalation may cause central nervous system effects. May cause cardiac arrhythmia. Vapours may cause drowsiness and dizziness.

Chronic Exposure : None known.

**Carcinogenicity**

No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP, IARC, or OSHA.

**SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**

Component	CAS-No.	Weight %
1-Chloro-1,2,2,2-tetrafluoroethane	2837-89-0	100.00

**SECTION 4. FIRST AID MEASURES**

Inhalation : Move to fresh air. If breathing is irregular or stopped, administer artificial respiration. Use oxygen as required, provided a qualified operator is present. Call a physician. Do not give drugs from adrenaline-ephedrine group.

Skin contact : After contact with skin, wash immediately with plenty of water. If there is evidence of frostbite, bathe (do not rub) with lukewarm (not hot) water. If water is not available, cover with a clean, soft cloth or similar covering. If symptoms persist, call a physician.

Eye contact : Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. In case of frostbite water should be lukewarm, not hot. If symptoms persist, call a physician.

Ingestion : Unlikely route of exposure. As this product is a gas, refer to the inhalation section. Do not induce vomiting without medical advice. Call a physician immediately.

**Notes to physician**

Treatment : Because of the possible disturbances of cardiac rhythm, catecholamine drugs, such as epinephrine, should be used with special caution and only in situations of emergency life support. Treatment of overexposure should be directed at the control of symptoms and the clinical conditions. Treat frost-bitten areas as needed.

**Genetron® 124**

Version 2

Revision Date 11/15/2007

Print Date 11/15/2007

**SECTION 5. FIRE-FIGHTING MEASURES**

- Flash point : not applicable
- Lower explosion limit : None
- Upper explosion limit : None
- Suitable extinguishing media : The product is not flammable.  
ASHRAE 34  
Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.  
Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
- Specific hazards during fire fighting : Contents under pressure.  
This product is not flammable at ambient temperatures and atmospheric pressure.  
However, this material can ignite when mixed with air under pressure and exposed to strong ignition sources.  
Container may rupture on heating.  
Cool closed containers exposed to fire with water spray.  
Do not allow run-off from fire fighting to enter drains or water courses.  
Vapours are heavier than air and can cause suffocation by reducing oxygen available for breathing.  
In case of fire hazardous decomposition products may be produced such as:  
Gaseous hydrogen chloride (HCl).  
Hydrogen fluoride  
Carbon monoxide  
Carbon dioxide (CO<sub>2</sub>)  
Carbonyl halides
- Special protective equipment for fire-fighters : In the event of fire and/or explosion do not breathe fumes.  
Wear self-contained breathing apparatus and protective suit.  
No unprotected exposed skin areas.

**SECTION 6. ACCIDENTAL RELEASE MEASURES**

- Personal precautions : Immediately evacuate personnel to safe areas.  
Keep people away from and upwind of spill/leak.  
Wear personal protective equipment. Unprotected persons must be kept away.  
Remove all sources of ignition.  
Avoid skin contact with leaking liquid (danger of frostbite).  
Ventilate the area.  
After release, disperses into the air.  
Vapours are heavier than air and can cause suffocation by reducing oxygen available for breathing.

**Genetron® 124**

Version 2

Revision Date 11/15/2007

Print Date 11/15/2007

Avoid accumulation of vapours in low areas.  
Unprotected personnel should not return until air has been tested and determined safe.  
Ensure that the oxygen content is  $\geq 19.5\%$ .

Environmental precautions : Prevent further leakage or spillage if safe to do so.  
The product evaporates readily.

Methods for cleaning up : Ventilate the area.

**SECTION 7. HANDLING AND STORAGE****Handling**

Handling : Handle with care.  
Avoid inhalation of vapour or mist.  
Do not get in eyes, on skin, or on clothing.  
Wear personal protective equipment.  
Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50 °C.  
Follow all standard safety precautions for handling and use of compressed gas cylinders.  
Use authorized cylinders only.  
Protect cylinders from physical damage.  
Do not puncture or drop cylinders, expose them to open flame or excessive heat.  
Do not pierce or burn, even after use. Do not spray on a naked flame or any incandescent material.  
Do not remove screw cap until immediately ready for use.  
Always replace cap after use.

Advice on protection against fire and explosion : The product is not flammable.  
Can form a combustible mixture with air at pressures above atmospheric pressure.

**Storage**

Requirements for storage areas and containers : Pressurized container: Protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use.  
Keep containers tightly closed in a dry, cool and well-ventilated place.  
Storage rooms must be properly ventilated.  
Ensure adequate ventilation, especially in confined areas.  
Protect cylinders from physical damage.

**SECTION 8. EXPOSURE CONTROLS / PERSONAL PROTECTION**

Protective measures : Do not breathe vapour.  
Avoid contact with skin, eyes and clothing.  
Ensure that eyewash stations and safety showers are close to

**Genetron® 124**

Version 2

Revision Date 11/15/2007

Print Date 11/15/2007

- the workstation location.
- Engineering measures : General room ventilation is adequate for storage and handling. Perform filling operations only at stations with exhaust ventilation facilities.
- Eye protection : Wear as appropriate:  
Safety glasses with side-shields  
If splashes are likely to occur, wear:  
Goggles or face shield, giving complete protection to eyes
- Hand protection : Leather gloves  
In case of contact through splashing:  
Protective gloves  
Neoprene gloves  
Polyvinyl alcohol or nitrile- butyl-rubber gloves
- Skin and body protection : Avoid skin contact with leaking liquid (danger of frostbite).  
Wear cold insulating gloves/face shield/eye protection.
- Respiratory protection : In case of insufficient ventilation wear suitable respiratory equipment.  
Wear a positive-pressure supplied-air respirator.  
Vapours are heavier than air and can cause suffocation by reducing oxygen available for breathing.  
For rescue and maintenance work in storage tanks use self-contained breathing apparatus.
- Hygiene measures : Handle in accordance with good industrial hygiene and safety practice.  
Ensure adequate ventilation, especially in confined areas.  
Avoid contact with skin, eyes and clothing.  
Remove and wash contaminated clothing before re-use.  
Keep working clothes separately.

**Exposure Guidelines**

1-Chloro-1,2,2,2-tetrafluoroethane	2837-89-0	WEEL	TWA	1,000 ppm
		HONEYWELL	TWA	1,000 ppm

**SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

- Form : Liquefied gas
- Color : colourless
- Odor : weak
- Molecular Weight : 136.47 g/mol
- pH : neutral

**Genetron® 124**

Version 2

Revision Date 11/15/2007

Print Date 11/15/2007

Melting point/range	: -199 °C (-326 °F)
Boiling point/boiling range	: -12 °C (10 °F)
Vapor pressure	: 3,399 hPa at 21.1 °C (70.0 °F)
Vapor pressure	: 8,694 hPa at 54.4 °C (129.9 °F)
Relative vapour density	: 4.7 (Air = 1.0)
Density	: 1.34 g/cm <sup>3</sup> at 30 °C (86 °F)
Water solubility	: no data available

**SECTION 10. STABILITY AND REACTIVITY**

Conditions to avoid	: Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50 °C. Decomposes under high temperature. Some risk may be expected of corrosive and toxic decomposition products. Can form a combustible mixture with air at pressures above atmospheric pressure. Do not mix with oxygen or air above atmospheric pressure.
Materials to avoid	: Finely divided aluminium Potassium Calcium Powdered metals Aluminium Magnesium Zinc
Hazardous decomposition products	: In case of fire hazardous decomposition products may be produced such as: Gaseous hydrogen chloride (HCl). Gaseous hydrogen fluoride (HF). Carbonyl halides Carbon monoxide Carbon dioxide (CO <sub>2</sub> )
Thermal decomposition	: >250 °C
Hazardous reactions	: Hazardous polymerisation does not occur. Stable under normal conditions.

**Genetron® 124**

Version 2

Revision Date 11/15/2007

Print Date 11/15/2007

**SECTION 11. TOXICOLOGICAL INFORMATION**

- Acute inhalation toxicity : LC50 rat  
Dose: 360000 ppm  
Exposure time: 4 h
- Repeated dose toxicity : rat  
NOEL: 15000 ppm
- Additional advice : Acute Health Hazard  
2-chloro-1,1,1,2- tetrafluoroethane. (HCFC-124): Cardiac sensitisation threshold (dog): 25000 ppm.  
Vapours are heavier than air and can cause suffocation by reducing oxygen available for breathing.  
Irritating to eyes and skin.  
Rapid evaporation of the liquid may cause frostbite.  
Avoid skin contact with leaking liquid (danger of frostbite).  
May cause cardiac arrhythmia.  
Chronic Health Hazard  
In vitro tests did not show mutagenic effects  
In vivo tests did not show mutagenic effects

**SECTION 12. ECOLOGICAL INFORMATION**

- Additional ecological information : Accumulation in aquatic organisms is unlikely.  
Avoid release into the atmosphere.  
This product contains greenhouse gases which may contribute to global warming. Do NOT vent to the atmosphere. To comply with provisions of the U.S. Clean Air Act, any residual must be recovered.  
This product is subject to U.S. Environmental Protection Agency Clean Air Act Regulations at 40 CFR Part 82.  
Section 611 requires the following label text on all shipments of this product:  
Warning: Contains Chlorotetrafluoroethane (HCFC-124), a substance which harms public health and environment by destroying ozone in the upper atmosphere.  
Refer to sections 610 and 612 for list of acceptable and unacceptable uses for this product.

**SECTION 13. DISPOSAL CONSIDERATIONS**

Waste Information: Avoid contact of spilled material and runoff with soil and surface waterways. Consult an environmental professional to determine if local, regional or national regulations would classify spilled or contaminated materials as hazardous waste. Use only approved transporters, recyclers, treatment, storage or disposal facilities. Dispose of according to all federal, state and local applicable regulations.

**Genetron® 124**

Version 2

Revision Date 11/15/2007

Print Date 11/15/2007

Other Disposal Considerations: Observe all Federal, State, and Local Environmental regulations.

The information offered here is for the product as shipped. Use and/or alterations to the product such as mixing with other materials may significantly change the characteristics of the material and alter the RCRA classification and the proper disposal method.

Additional advice : This product is subject to U.S. Environmental Protection Agency Clean Air Act Regulations Section 608 in 40 CFR Part 82 regarding refrigerant recycling.

**SECTION 14. TRANSPORT INFORMATION**

**DOT** Proper shipping name : 1-Chloro-1,2,2,2-tetrafluoroethane  
UN-Number : 1021  
Class : 2.2  
Packing group :

**IATA** UN Number : 1021  
Description of the goods : 1-Chloro-1,2,2,2-tetrafluoroethane  
Class : 2.2  
Hazard Label : 2.2  
Packing instruction (cargo aircraft) : 200  
Packing instruction (passenger aircraft) : 200

**IMDG** Substance No. : UN 1021  
Description of the goods : 1-Chloro-1,2,2,2-tetrafluoroethane  
Class : 2.2  
Hazard Label : 2.2  
EmS Number : F-C  
Marine pollutant : no

**SECTION 15. REGULATORY INFORMATION****Inventories**

EU. EINECS : On or in compliance with the inventory

US. Toxic Substances Control Act : On TSCA Inventory

Australia. AICS : On or in compliance with the inventory

Canada. Canadian Environmental Protection Act (CEPA). Domestic Substances List (DSL). (Can. Gaz. Part II, Vol. 133) : This product contains the following components that are not on the Canadian DSL nor NDSL lists.

Japan. ENCS : 1-Chloro-1,2,2,2-tetrafluoroethane 2837-89-0  
: On or in compliance with the inventory

**Genetron® 124**

Version 2

Revision Date 11/15/2007

Print Date 11/15/2007

Korea. KECI : On or in compliance with the inventory

Philippines. PICCS : On or in compliance with the inventory

China. IECSC : On or in compliance with the inventory

Switzerland. Consolidated Inventory : On or in compliance with the inventory

New Zealand. Interim Inventory of Chemicals (as published by ERMA new Zealand) : On or in compliance with the inventory

**National regulatory information****SARA 313 Components** : 1-Chloro-1,2,2,2-tetrafluoroethane 2837-89-0**SARA 311/312 Hazards** : Acute Health Hazard  
Sudden Release of Pressure Hazard**California Prop. 65** : This product does not contain any chemicals known to State of California to cause cancer, birth, or any other reproductive defects.**New Jersey RTK** : 1-Chloro-1,2,2,2-tetrafluoroethane 2837-89-0**Pennsylvania RTK** : 1-Chloro-1,2,2,2-tetrafluoroethane 2837-89-0**Global warming potential** : 470**Ozone depletion potential (ODP)** : 0.02**SECTION 16. OTHER INFORMATION**

	<b>HMIS III</b>	<b>NFPA</b>
Health Hazard	: 1	2
Flammability	: 1	1
Physical Hazard	: 0	
Instability	:	0

**Genetron® 124**

Version 2

Revision Date 11/15/2007

Print Date 11/15/2007