



The MSDS format adheres to the standards and regulatory requirements of Canada and may not meet regulatory requirements in other countries.

DuPont
Material Safety Data Sheet

Page 1

"SUVA" 409A
CEF0409A Revised 29-OCT-2002

CHEMICAL PRODUCT/COMPANY IDENTIFICATION

Material Identification

Formula : CHCLF2/CHCLFCF3/CH3CCLF2
Molecular Weight : 97.45
CAS Name : FORANE (R) FX-56 GENETRON 409A

Tradenames and Synonyms

HCFC BLEND OF HCFC-22, HCFC-124 & HCFC-142b
"SUVA" is a registered trademark of E.I. du Pont de Nemours and Company. DuPont Canada Inc. is a licensee.

Company Identification

MANUFACTURER/DISTRIBUTOR
DuPont Canada, Inc.
P.O. Box 2200
Streetsville
Mississauga, Ontario L5M 2H3

PHONE NUMBERS

Product Information : 1-800-387-2122
Transport Emergency : 1-613-348-3616 (24 HOURS)
Medical Emergency : 1-613-348-3616 (24 HOURS)

COMPOSITION/INFORMATION ON INGREDIENTS

Components

Material	CAS Number	%
*CHLORODIFLUOROMETHANE (HCFC-22)	75-45-6	60 WT%
*1-CHLORO-1,1-DIFLUOROETHANE (HCFC-142b)	75-68-3	15 WT%
*ETHANE, 2-CHLORO-1,1,1,2-TETRAFLUORO (HCFC-124)	2837-89-0	25 WT%

* Disclosure as a toxic chemical is required under Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR part 372.

HAZARDS IDENTIFICATION

Potential Health Effects

INHALATION: Immediate effects of overexposure may cause central nervous system depression with dizziness, confusion, incoordination, drowsiness or unconsciousness. Gross overexposure may cause: Irregular heart beat with a strange sensation in the chest, "heart thumping", apprehension, lightheadedness, feeling of fainting, dizziness, weakness, sometimes progressing to loss of consciousness and death. Other effects include: Suffocation, if air is displaced by vapors or fatality from gross over-exposure. Decomposition products are hazardous.

SKIN CONTACT: Short-term overexposure may cause frostbite, if liquid or escaping vapor contacts the skin. Repeated and/or prolonged exposure may cause: Defatting of the skin with itching, redness or rash.

EYE CONTACT: Contact with the vapor or aerosol may cause eye irritation with tearing, pain, blurred vision or "frostbite-like" effects.

ADDITIONAL HEALTH EFFECTS: Increased susceptibility to the effects of this material may be observed in persons with pre-existing disease of the: central nervous system, cardiovascular system.

Carcinogenicity Information

None of the components present in this material at concentrations equal to or greater than 0.1% are listed by IARC, NTP, OSHA or ACGIH as a carcinogen.

FIRST AID MEASURES

First Aid

INHALATION

If inhaled, immediately remove to fresh air. Keep person calm. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Call a physician.

SKIN CONTACT

Flush area with lukewarm water. Do not use hot water. If frostbite has occurred, call a physician.

EYE CONTACT

In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Call a physician.

(FIRST AID MEASURES - Continued)

INGESTION

Ingestion is not considered a potential route of exposure.

Notes to Physicians

THIS MATERIAL MAY MAKE THE HEART MORE SUSCEPTIBLE TO ARRHYTHMIAS. Catecholamines such as adrenaline, and other compounds having similar effects, should be reserved for emergencies and then used only with special caution.

FIRE FIGHTING MEASURES

Flammable Properties

Flash Point	No flash point
Flammable limits in Air, % by Volume	
LEL	Non per ASTM E681
UEL	Non per ASTM E681

Fire & Explosion Hazards:

Cylinders may rupture under fire conditions. Decomposition may occur.

Contact of welding or soldering torch flame with high concentrations of refrigerant can result in visible changes in the size and color of torch flames. This flame effect will only occur in concentrations of product well above the recommended exposure limit, therefore stop all work and ventilate to disperse refrigerant vapors from the work area before using any open flames.

409A is not flammable at temperatures up to 100 deg C (212 deg F) at atmospheric pressure. However, mixtures of "Suva" 409A with high concentrations of air at elevated pressure and/or pressure can become combustible in the presence of an ignition source. R-409A can also become combustible in an oxygen enriched environment (oxygen concentrations greater than that in air). Whether a mixture containing R-409A and air, or R-409A in an oxygen enriched atmosphere becomes combustible depends on the inter-relationship of 1) the temperature 2) the pressure, and 3) the proportion of oxygen in the mixture. In general, R-409A should not be allowed to exist with air above atmospheric pressure or at high temperatures or in an oxygen enriched environment. For example: R-409A should NOT be mixed with air under pressure for leak testing or other purposes.

Experimental data have also been reported which indicate

(FIRE FIGHTING MEASURES - Continued)

combustibility of HCFC-22, a component in this blend, in the presence of chlorine.

Extinguishing Media

Water Spray, Water Fog, CO2, Dry Chemical, Water.

Fire Fighting Instructions

Wear self-contained breathing apparatus (SCBA) and full protective equipment. Cool tank/container with water spray. Keep personnel removed and upwind of fire. Shut off source of fuel, if possible and without risk.

Water runoff should be contained and neutralized prior to release.

Hydrogen fluoride or hydrogen chloride fumes emitted during a fire can react with water to form hydrofluoric acid or hydrochloric acid. Wear neoprene gloves when handling refuse from fire.

ACCIDENTAL RELEASE MEASURES

Safeguards (Personnel)

NOTE: Review FIRE FIGHTING MEASURES and HANDLING (PERSONNEL) sections before proceeding with clean-up. Use appropriate PERSONAL PROTECTIVE EQUIPMENT during clean-up.

Spill Clean Up

Dispose of in an approved container.

Accidental Release Measures

Ventilate area using forced ventilation, especially in low or enclosed places where heavy vapors might collect. Remove open flames. Use self-contained breathing apparatus (SCBA) for large spills or releases.

HANDLING AND STORAGE

Handling (Personnel)

Do not get in eyes, on skin or clothing. Do not breathe vapor or mist. Use with sufficient ventilation to keep employee exposure below recommended limits. Wash contaminated clothing prior to reuse.

(HANDLING AND STORAGE - Continued)

Handling (Physical Aspects)

Keep away from heat, sparks and flames. Open container only in well-ventilated area.

Storage

Keep away from heat, sparks and flames. Store in a well ventilated area away from heat and sunlight.

Close container after each use.

Store below 120 deg F (49 deg C).

EXPOSURE CONTROLS/PERSONAL PROTECTION

Engineering Controls

Use only with adequate ventilation especially for enclosed and low area where vapors can accumulate.

Personal Protective Equipment

EYE/FACE PROTECTION

Wear coverall chemical splash goggles.

RESPIRATORS

Wear NIOSH approved respiratory protection, as appropriate.

PROTECTIVE CLOTHING

Where there is potential for skin contact have available, and wear as appropriate, impervious gloves, apron, pants, and jacket.

Lined butyl gloves should be used to avoid prolonged or repeated exposure.

Exposure Guidelines

Applicable Exposure Limits

CHLORODIFLUOROMETHANE (HCFC-22)

PEL (OSHA)	: None Established
TLV (ACGIH)	: 1,000 ppm, 3,540 mg/m ³ , 8 Hr. TWA, A4
AEL * (DuPont)	: None Established

1-CHLORO-1,1-DIFLUOROETHANE

(Applicable Exposure Limits - Continued)

PEL (OSHA) : None Established
 TLV (ACGIH) : None Established
 AEL * (DuPont) : 1000 ppm, 8 Hr. TWA
 WEEL (AIHA) : 1000 ppm, 8 Hr. TWA

ETHANE, 2-CHLORO-1,1,1,2-TETRAFLUORO
 PEL (OSHA) : None Established
 TLV (ACGIH) : None Established
 AEL * (DuPont) : 1000 ppm, 8 & 12 Hr. TWA
 WEEL (AIHA) : 1000 ppm, 8 Hr. TWA

* AEL is DuPont's Acceptable Exposure Limit. Where governmentally imposed occupational exposure limits which are lower than the AEL are in effect, such limits shall take precedence.

 PHYSICAL AND CHEMICAL PROPERTIES

Physical Data

Boiling Point : -31 F (-35 C)
 Vapor Density : 3.36 (Air=1.0)
 Solubility in Water : Negligible
 Specific Gravity : 1.215 @ 70 F (21 C)
 Vapor Pressure : 107 psia @ 70 F (21 C)
 % Volatiles : 100 %
 Odor : Faint, Ethereal, Ether.
 Form : Liquified Gas.
 Color : Clear, Colorless.

 STABILITY AND REACTIVITY

Chemical Stability

Stable.

Conditions contributing to instability: Thermal decomposition due to exposure to heat (>800 deg F) or fire.

Conditions to Avoid

Avoid flames, sparks, extremely hot metal, heating elements, pilot lights, static electricity, combustion engines, ignition sources, etc.

Incompatibility with Other Materials

Avoid contact with strong alkali or alkaline earth metals, finely powdered metals such as aluminum, magnesium or zinc and strong oxidizers since they may react with or accelerate decomposition of this material.

(STABILITY AND REACTIVITY - Continued)

Decomposition

Thermal decomposition products include hydrogen fluoride, hydrogen chloride, carbon monoxide, carbon dioxide and chlorine and possibly carbonyl halides.

TOXICOLOGICAL INFORMATION

Animal Data

CHLORODIFLUOROMETHANE (HCFC-22)

INHALATION: 4 hour, LC50, rat: 220,000 ppm

Animal testing indicates this material is a slight eye and skin irritant, but not a skin sensitizer.

INGESTION: Long-term exposure caused: No significant toxicological effects.

Single exposure to high doses caused: Central nervous system depression. Inactivity or anaesthesia. Lung noise. Altered respiratory rate. Histopathological changes of the liver. Cardiac sensitization, a potentially fatal disturbance of heart rhythm associated with a heightened sensitivity to the action of epinephrine. Repeated exposure caused: No significant toxicological effects. Long-term exposure caused: Reduced weight gain. Increased adrenals, kidney, liver, pituitary weight.

ADDITIONAL TOXICOLOGICAL EFFECTS:

In chronic inhalation studies, HCFC-22, at a concentration of 50,000 ppm (v/v), produced a small, but statistically significant increase of late-occurring tumors involving salivary glands in male rats, but not female rats or male or female mice. In the same studies, no increased incidence of tumors was seen in either species at concentrations of 10,000 ppm or 1000 ppm (v/v). Animal data show developmental effects only at exposure levels producing other toxic effects in the adult animal. This material is not considered a unique developmental hazard to the conceptus. Reproductive data on male animals show: No change in reproductive performance. Specific studies to evaluate the effect on female reproductive performance have not been conducted; however, limited information obtained from studies on developmental toxicity do not indicate adverse effects on female reproductive performance. This material produces genetic damage in bacterial cell cultures. In mammalian cell cultures and animals, this material has not produced genetic toxicity. In animal testing, this material has not caused permanent genetic damage in reproductive cells of mammals (has not produced heritable genetic

(TOXICOLOGICAL INFORMATION - Continued)

damage).

1-CHLORO-1,1-DIFLUOROETHANE (HCFC-142b)

Inhalation 2 hour LC50: 447,642 ppm in rats

The compound is untested for skin irritancy, is not an eye irritant, and is untested for animal sensitization.

Inhalation: Toxic effects of single inhalation exposures include respiratory irritation, loss of reflexes, and unconsciousness. Cardiac sensitization was seen in dogs exposed to concentrations of 5% and higher. Exposure of dogs or monkeys to concentrations of 5 to 20% for five minutes caused decreased blood pressure (hypotension). Repeated exposure produced only irritation of the lungs.

Tests in animals demonstrate no carcinogenic, developmental, or reproductive toxicity.

The compound does not produce genetic damage in animals or in bacterial and mammalian cell cultures. It does not produce heritable genetic damage.

ETHANE, 2-CHLORO-1,1,1,2-TETRAFLUORO (HCFC-124)

INHALATION: 4 hour, ALC, rat: 230,000 - 300,000 ppm.

Single exposure caused: Cardiac sensitization, a potentially fatal disturbance of heart rhythm associated with a heightened sensitivity to the action of epinephrine. Lowest-Observed-Adverse-Effect-Level for cardiac sensitization: 25,000 ppm. Single exposure caused: the following temporary effects - Inactivity or anaesthesia. Low blood pressure. Repeated exposure caused: Decreased body weight. Altered clinical chemistry. These effects were reversible. Repeated exposure caused: the following temporary effects - Inactivity or anaesthesia. Lethargy. Incoordination. Altered respiratory rate. One study showed: Increased liver weight.

CARCINOGENIC, DEVELOPMENTAL, REPRODUCTIVE, MUTAGENIC EFFECTS:

In animal testing this material has not caused carcinogenicity, developmental toxicity. No animal data are available to define the following effects of this material: reproductive toxicity. Tests have shown that this material does not cause genetic damage in bacterial or mammalian cell cultures, or in animals. This material has not been tested for its ability to cause permanent genetic damage in reproductive cells of mammals (not tested for heritable genetic damage).

ECOLOGICAL INFORMATION

Ecotoxicological Information

AQUATIC TOXICITY:

CHLORODIFLUOROMETHANE (HCFC-22)
48 hour EC50 - Daphnia magna: 433 mg/L

DISPOSAL CONSIDERATIONS

Waste Disposal

Recycle or reclaim if possible. Reclaimed material may be incinerated but toxic and corrosive combustion products (HF and HCL) must be handled appropriately.

Consult Federal, State or local authorities for proper disposal procedures.

TRANSPORTATION INFORMATION

Shipping Information

DOT/IMO/IATA
Proper Shipping Name : LIQUEFIED GAS, N.O.S.
(CHLORODIFLUOROMETHANE,
CHLOROTETRAFLUOROETHANE)
Hazard Class : 2.2
UN No. : UN 3163
DOT/IMO Label : NONFLAMMABLE GAS

Shipping Information -- Canada

TDG
Proper Shipping Name : Liquefied Gas, N.O.S.
(Chlorodifluoromethane
Chlorotetrafluoroethane)
TDG Class : 2.2
UN # : 3163

REGULATORY INFORMATION

Canadian Regulations

WHMIS Classification:

CLASS A Compressed Gas

CLASS D Division 2 Subdivision B - Toxic Material. Skin or Eye Irritant.

(REGULATORY INFORMATION - Continued)

This product has been classified in accordance with the hazard criteria of the CPR and the MSDS contains all the information required by the CPR.

CEPA Status : DSL: REPORTED/INCLUDED.

 OTHER INFORMATION

The data in this Material Safety Data Sheet relates only to the specific material designated herein and does not relate to use in combination with any other material or in any process.

Responsibility for MSDS

FLUOROPRODUCTS
 DuPont Canada Inc.
 Box 2200, Streetsville
 Mississauga, Ontario, L5M 2H3
 (905) 821-5925.

This information is based upon technical information believed to be reliable. It is subject to revision as additional knowledge and experience is gained.

End of MSDS